

MEDIUM DUTY UTILITY BREAKER

Rugged, lightweight and powerful construction designed for light to medium duty operation. They excel at curb and sidewalk demolition, asphalt cutting, and are popular for ground rod driving with electric utilities.

Feathering on/off valve allows the operator to control the output energy of the tool through the full range from 1 to 1525 blows per minute, making startup and initial tool placement easy.

Diaphragm type accumulator design provides for ease of maintenance and extended service life of the tool. All models operate at a maximum back pressure of 250 psi (17 bar) on open center systems.



- Reduce Operator Fatigue
- Increase Productivity
- Handles Tough Applications
- Easy Operator Control
- Easy Maintenance

SPECIFICATIONS

Part Number		08-000-10	
Output	0 - 1525 Blows Per Minute		
Input Flow Range	7 - 9 gpm	26 - 34 lpm	
Input Pressure	1500 - 2000 psi	105 - 140 bar	
Max. Back Pressure	250 psi	17 bar	
Optimum Flow	8 gpm	30 lpm	
Porting	-8 SAE O-Ring		
Connector	3/8in. Male Pipe Head Hose End		
Steel Capacity	4-1/4 x 1 in. Hex*, 6 x 1-1/8 in. Hex and 6 x 1-1/4 in. Hex		
Weight	45 / 51 lb	20 / 23 kg	
Length	25 in.	65 cm	
Width (At Handles)	14 / 17.5 in.	35 / 45 cm	